

access

LIGHTING

Read & Save these Instructions Model: 50565 Installation & Operation Instructions

(1) TOOLS AND MATERIALS REQUIRED

- ❖ BLADE SCREW DRIVER
- ❖ WIRE CUTTERS
- ❖ WIRING SUPPLIES AS REQUIRED BY ELECTRICAL CODE
- ❖ 1 x 60W/E12/Candelabra Base Bulb

Attention:

Before assembling your lighting fixture, please read the following instructions. If you feel you do not have sufficient electrical experience, refer to a do-it-yourself wiring handbook or have your fixture installed by a qualified licensed electrician.

(2) GENERAL

1. To ensure the success of the installation, be sure to read these instructions and review the diagrams thoroughly before beginning.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
3. These fixtures are intended for mounting to a standard 4" x 2 1/4" deep metal octagon outlet box. The box must be directly supported by the building structure and U.L. Recognized.
4. Before commencing with the installation, **disconnect the power by turning off the circuit breaker** or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

NOTE:

The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. These factors must be supplied by the person(s) caring for and operating the fixture.

(3) UNPACKING THE FIXTURE

On checking the contents of the box you will find;

- ❖ Back Plate
- ❖ Mounting Hardware
- ❖ Fixture Plate with socket
- ❖ 1 x Glass Shade

(4) PREPARE THE FIXTURE

Refer to attached illustration of fixture parts and assembly.

1. If you are replacing an existing fixture disconnect and remove the old fixture. Expose the supply wiring from the outlet box.
2. Secure the **Back Plate** to the junction box with the supplied **Mounting Screws (1)**.
3. Pull the Supply wires through the **Center Hole** in the **Back Plate**.
4. Connect the **BLACK** supply wire to the **Black** wire of the fixture with supplied **Wire Nuts (2)** ensuring a secure connection.
5. Connect the **WHITE** supply wire to the **White** wire from the fixture a secure with supplied **Wire Nuts (2)**.
6. Attach the **ground (GREEN)** wire from the fixture to the **outlet box ground terminal** (or to the box ground wire).
7. Secure all wire nuts connections with **UL listed electrical tape**. **Tuck wires carefully into Junction box**.
8. Position the **Fixture Plate with Socket** over the **Back Plate** allowing the two holes on the top and bottom of the **Plates** to align. Secure with the supplied **Screws (3)**.
9. Insert **1 x 60W/E12/Candelabra Base Bulb (4)**. **DO NOT EXCEED WATTAGE SPECIFIED ON WARNING LABEL**
10. Fit the **Glass Shade (5)** over the sockets. Secure by sliding the shade into the slot.
11. Restore electricity and check the operation of your new lighting fixture.

CAUTION:

- **Ensure that the Fitting is Cool and Switched off, Before Changing the Bulb.**
- **Do Not use Bulbs Exceeding Maximum Wattage, As Per Caution Label.**
- **Do not Place the Fixture in Close Proximity to Combustible Material**

61408PV1

MODEL 50565

