



Narrow LED Striplight CRDL Series

Features

This clean appearance, surface mounted cloud provides a wide distribution of light with a white diffuser. It can be used in various applications including offices, corridors, garages, kitchens and public spaces. Fixture mounts to standard junction box (not included).

Construction

Housing is die-formed of 22-gauge steel. Standard mounting holes are included. Power supply connections can be made inside the fixture wire way or in a junction box (not included).

Finish

Housing is finished in lighting grade white baked gloss enamel paint.

Diffuser

White acrylic diffuser.

Electrical

This unit is direct wired with a constant current low voltage electronic LED driver. 120-277V universal voltage (non-dimmable) driver.

LED

Integrated LED modules capable of producing:

- 24" - 17W, 1900 source lumens
- 46" - 22W, 2400 source lumens
- 46" - 43W, 4700 source lumens
- 4000K (CCT)
- Rated for 50,000 hours, 80 CRI

Certification

cETLus listed for damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.

LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		



Ordering Information:

Cool White	LED	Source Lumens	CCT	L	W	H
CRDL022419L40MVWH	17W	1900	4000K	24"	2-1/2"	2-1/2"
CRDL024624L40MVWH	22W	2400	4000K	46-1/2"	2-1/2"	2-1/2"
CRDL024647L40MVWH	43W	4700	4000K	46-1/2"	2-1/2"	2-1/2"