

AXEL Vanity

3-552-xx

oxygen

FIXTURE TYPE _____ LOCATION _____
 PROJECT _____ DATE _____




-20 Polished Nickel



-24 Satin Nickel

LIGHT SOURCE 1 x 11.7W LED, 3000K, CRI 90
LUMINAIRE POWER 14.2W at 120V
RATED LIFE 60000 hr RL
OPTIONAL COLOR TEMPERATURES 2700K, 3500K, 4000K
LUMEN OUTPUT Delivered: 1297 lm (LM-79)
INPUT VOLTAGE 120V to 277V AC, 50/60Hz
DRIVER OUTPUT 350mA, 14.7W max power
DIMMING TRIAC and ELV dimming at 120V AC; 0-10V dimming, 100% to 1% current output
CONSTRUCTION Plated Steel and Acrylic
DIFFUSER - Matte White Acrylic
FINISHES Polished Nickel (-20), Satin Nickel (-24)
MOUNTING 4" Square J-Box* with a single device mud ring
 *Deep J-Box (Required to house driver)
STANDARDS UL Dry/Damp listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W: 29.00"
H: 3.50"
Ext: 2.75"
M.C: 1.75" from top of fixture

Order example for standard fixture:

3-552-24 (x- Voltage - xxx-Sequence # - xx-Finish)

3: 120V to 277V

Order example for optional color temperatures: **3-552-2724**

27: 2700K, **35:** 3500K, **40:** 4000K

