

**ELITE Ceiling Mount**  
**3-644-xx**

oxygen

FIXTURE TYPE \_\_\_\_\_

LOCATION \_\_\_\_\_

PROJECT \_\_\_\_\_

DATE \_\_\_\_\_



-15 Black



-22 Oiled Bronze



-24 Satin Nickel



-6 White

**LIGHT SOURCE** 1 x 11W LED with Driver on board, 3000K, CRI 90

**LUMINAIRE POWER** 12.3W at 120V

**RATED LIFE** 50000 hr RL

**OPTIONAL COLOR TEMPERATURES** 3000K Only

**LUMEN OUTPUT** Delivered: 592 lm (LM-79)

**INPUT VOLTAGE** 120V AC, 50/60Hz

**DRIVER OUTPUT** N/A

**DIMMING** TRIAC Dimming



**CONSTRUCTION** Cast Aluminum Housing

**DIFFUSER** - Etched White Glass

**FINISHES** White (-6), Black (-15),  
Oiled Bronze (-22), Satin Nickel (-24)

**MOUNTING** 4" Octagonal J-Box

**STANDARDS** ETL Wet listed, Conforms to UL STD 1598,  
Certified CAN/CSA STD C22.2 No 250.0.



**DIMENSIONS**

**Dia:** 5.50"

**H:** 1.00"

Note: For wet locations, installer must provide a bead of caulk between fixture housing and mounting surface.

Order example for standard fixture:  
**3-644-15** (x- Voltage - xxx-Sequence # - xx-Finish)  
3: 120V Only

