

LED Bulkheads

Wall or ceiling mounted • Wet location listed



Description:

One-Light 9-1/2" LED Wall or Ceiling Bulkhead. General purpose LED luminaire comprised of a die-cast aluminum frame and polycarbonate diffuser. Fixtures are impact resistant and can be mounted on wall or ceiling. Replaceable LED module. Black finish.

Specifications:

- Black (-31) (powder coat paint)
- Aluminum Construction
- White polycarbonate diffuser
- LED Module is replaceable (part # 93053641)
- Robust and energy efficient.
- Offers various mounting options.
- Can be widely adapted for indoor and outdoor applications.
- 1,211 lumens 71.2 lumens/watt per module (source)
- 3000K color temperature, 90+ CRI.
- Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

| | |
|------------------------|---|
| Number of Modules | 1 |
| Input Power | 17w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 1211/71.2 (LM-82) |
| Lumens/LPW (Delivered) | 922/54.6 (LM-79) |
| CCT | 3000 K |
| CRI | 90 CRI |
| Life (hours) | 60,000 (L70/TM-21) |
| FCC | Meets FCC Title 47, Part 15 Class B |
| Min. Start Temp | -30 °C |
| Max. Operating Temp | 30 °C |
| Warranty | 5 year warranty |
| Labels | cCSAus Wet location listed |
| | ENERGY STAR® qualified |
| | Meets California Title 24 high efficacy requirements for outdoor use only |

P3650-3130K9

Images:



Dimensions:

Diameter: 9-1/2"
 Depth: 4-11/16"
 Height: 9-1/2"
 H/CTR: 4-3/4"

Glass
 Width: 9-3/16"
 Length: 9-3/16"
 Height: 3-5/8"

P3650-3130K9

Dimming Notes:

P3650 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

| | | |
|---------|---------------|------------|
| Lutron | Nova T | NTELV-300 |
| Lutron | Vierti | VTELV-600 |
| Lutron | Maestro | MAELV-600 |
| Lutron | spacer/system | SPSELV-600 |
| Leviton | Renoir II | AWRMG-EAW |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.