

PE2WL SERIES

Wet Location LED Emergency Unit

Specifications:

Description:

The PE2WL offers LED performance and value with a compact and attractive wet location LED based emergency light. The grey housing is made of corrosion resistant UV stabilized polycarbonate. Lamp-head consists of metalized high-performance reflector and 15 ultra-bright LED's with tempered glass lens. Includes external mounting brackets for ease of installation. The PE2WL has adequate capacity to run 1 each PEWLH double head or 2 PEWLH single-head remotes at 9.6 VDC for 90 minutes.

Features:

- LED life-cycle of more than 10 years
- Quick installation
- Dual-voltage 120/277V AC input
- Includes long-life 9.6 VDC Nickel Cadmium battery for UL recognized 90 minute operation
- Remote capacity for extended runtime
- Wet Location Listed (0°C to 50°C)
- Fully adjustable lamp-heads
- Provided with water-proof test switch and AC-on indicator

Application:

The PE2WL can be applied in areas that are susceptible to rain and severe moisture like pool areas, parking decks, and other commercial applications.

Energy Consumption:

| Input | 120 VAC | 277 VAC |
|-------|---------|---------|
| Watts | 2.7W | 2.7W |
| Amps | 0.03A | 0.013A |

Accessories:


- PEWLH – SG – 82
- PEWLH – DB – 82



Images:



Dimensions:



Warranty:

2 year full unit warranty

Compliances:

- UL924 Listed for Wet Location
- NFPA 101 and NFPA 70
- OSHA

Catalog number:

| Base | Material | Input | Finish |
|-------|---------------|---------|--------------------|
| PE2WL | Thermoplastic | 120/277 | 82 - Metallic Gray |