

OUTDOOR TAPE 12V

8011, 8051, 8101

WAC


LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project: _____

Location: _____



PRODUCT DESCRIPTION

Flexible tape light with UV stabilized silicone seals that protect against water and dusts.

FEATURES

- Conveniently adapts into existing 12V system
- IP 68 rated for submersible up to 5 feet
- May be tied into any 12V landscape lighting system
- Maximum of 40 ft per run to stay within 5 amps
- Flexible linear lights maybe cut to desired length at the end of the run
- Various lengths may be joined together with IP68 rated connectors
- UV-stabilized silicone seals and protects the tape sections
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

SPECIFICATIONS

Input: 9-15VAC (Transformer is required)
Power: 2W / 2.1VA
Brightness: 115 lm
CRI: 85
Rated Life: 60,000 hours
Operating Temp: -40°F(-40°C) to 122°F(50°C)
 at relative humidity 95%

ORDERING NUMBER

		Color Temp		Finish	
8011	1 foot	27	2700K	BK	Black tape color
8051	5 feet		3000K		
8101	10 feet				

_____ - _____ **BK**

Example: **8011-30BK**

waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

OUTDOOR TAPE 12V ACCESSORIES

8011, 8051, 8101

WAC

LANDSCAPE LIGHTING

Clear channel



LED-TO24-CH5

5 feet

Includes mounting hardware

End cap



LED-TO24-EC

Surface mounting clip



LED-TO24-C1

Secures on both edges
(10 Qty)

Edge mounting clip



LED-TO24-C2

Secures on one edge
(10 Qty)

Invisible clip



LED-TO24-C3

Spring clip secures
beneath tape (10 Qty)

Lead wire with 5A fuse
40 ft max tape run



Protects tape sections
from over current

8000-06BK

6 feet

8000-10BK

10 feet

Joiner Cable - Short



8001-6BK

6 inch

8001-12BK

1 foot

Joiner Cable - Long



8001-72BK

6 feet

8001-120BK

10 feet

4 Way "X" Connector



8003-BK

3 Way "Y" Connector



8002-BK

Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed
See transformer spec sheet for details and its accessories

9075-TRN-SS

75W Max

9150-TRN-SS

150W Max

9300-TRN-SS

300W Max

9600-TRN-SS

600W Max



waclighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760

OUTDOOR TAPE 12V ACCESSORIES

8011, 8051, 8101

WAC

LANDSCAPE LIGHTING

TESTED MAGNETIC LOW VOLTAGE (MLV) DIMMERS

Luminaire	Dimmer					
	Manufacturer	Family	Model	Power Rating	Range*	Note
8011 8051 8101	Lutron	Diva	DVLV-600	600W	33% - 100%	Output maxes at 50% dimming level
		Skylark	SLV-600P	600W	28% - 100%	Output maxes at 50% dimming level
		Skylark	S-10P	1000W		Not recommended

*Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760